

CLAIMS

1. Drive arrangement of a wiper device for windows of motor vehicles with at least two swivel-mounted wiper arms (18, 20) that are connected to one another via a crank mechanism, wherein one of the wiper arms (18) is directly coupled with a driven shaft (16) of an electromotive drive (10).
2. Drive arrangement according to Claim 1, characterized in that the electromotive drive (10) includes a uniformly transmitting gear (14).
3. Drive arrangement according to Claim 1 or 2, characterized in that an electric driving motor (12) of the drive (10) features rotational direction reversal.
4. Drive arrangement according to Claim 3, characterized in that a reversal of the rotational direction of the electromotive drive (10) is provided for at each end of travel of the wiper arms (18, 20).
5. Drive arrangement according to one of the preceding claims, characterized in that the electromotive drive (10) features a sensory mechanism to detect the end of travel.
6. Drive arrangement according to one of the preceding claims, characterized in that the electromotive drive (10) features a speed control.
7. Drive arrangement according to Claim 6, characterized in that the speed control always provides for a reduction in the rotational speed of the drive (10) near the ends of travel of the wiper arms (18, 20).
8. Drive arrangement according to one of the preceding claims, characterized in that at least two wiper arms (18, 20) are coupled via a crank and rocker linkage (30).

9. Drive arrangement according to Claim 8, characterized in that both of the wiper arms (18, 20) feature a path of motion in the same direction.
10. Drive arrangement according to one of the preceding claims, characterized in that at least two wiper arms (18, 20) feature an approximately parallel path of motion.